

8-Port Gigabit Unmanaged Ethernet Switch

Product Overview

UTP1308 is a full gigabit Ethernet switch product, which provides five 10/100/1000Mbps adaptive RJ45 ports and supports wire speed forwarding on all ports. Based on gigabit Ethernet network technology, it effectively avoids network transmission bottleneck and has good network adaptability. Green Ethernet technology (802.3az) is adopted to automatically adjust signal strength by detecting cable length and workload, effectively reduce energy consumption and protect the environment without reducing equipment operation performance and efficiency. The switch is easy to install and use. It is suitable for expanding your home or office network. The LED on the front panel can dynamically display the operation status of the network.

Features and Highlights


- Comply with IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x, IEEE802.3az standards
- Supports IEEE802.3x flow control for Full-duplex Mode and backpressure for Half-duplex Mode
- Supports MAC address auto-learning
- 8 x 10/100/1000Mbps Auto-Negotiation RJ45 ports supporting Auto-MDI/MDIX
- UTP port supports automatic negotiation function and automatically adjusts transmission mode and rate
- Store and forward mode operates
- LED indicators for monitoring power, link/activity
- External power adapter supply, exquisite design, easy to use.




Product Specifications

| | | |
|-------------------------|---------------------------------------|---|
| Model Name | | UTP1308 |
| Standards and Protocols | | IEEE 802.3i, IEEE 802.3u, IEEE802.3ab, IEEE802.3x, IEEE802.3az |
| Interface | | 8 x 10/100/1000Mbps adaptive RJ45 port (Auto MDI/MDIX) |
| Network Media | | 10BASE-T: UTP category 3,4 cable (maximum 100m) 100BASE-TX: UTP category 5,5e cable (maximum 100m) 1000Base-T: UTP category 5, 5e,6 cable (maximum 100m) |
| Transfer Method | | Store-and-Forward |
| MAC Address Table | | 8K |
| Switching Capacity | | 16Gbps |
| Packet Forwarding Rate | | 11.9Mpps |
| Packet Buffer | | 4Mbits |
| Jumbo Frame | | 15KBytes |
| Indicators | Per Device | Power: Green |
| | Per Port | Link/Act: Green |
| Power Specifications | | 5V 1A Adapter |
| Dimensions (L×W×H) | | 140*67*26mm |
| EMS | FCC 47 CFR Part 15 Class A | |
| | EN55032 Class A | |
| | IEC61000-4-5, line to ground 4kV | |
| | IEC61000-4-6, level 2 (0.15MHz~80MHz) | |
| LVD | EN 62368-1: 2014 | |
| | EN 62328-A11:2017 | |
| Environment | | Operating Temperature: 0°C~40°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% RH non-condensing Storage humidity: 5%~90% RH non-condensing |

Product Appearance



Dimensions



Front View



Back View

SHENZHEN UTEPO TECH LTD.

C2301, Block BC, Union R&D Center, Longteng Community, XixiangStreet,Bao'an District, Shenzhen, Guangdong, China
Email: info@utepo.net (Sales), support@utepo.net (Technical support)

©2024 SHENZHEN UTEPO TECH LTD. All Rights Reserved.
Version,V2.0, updated 2024.12.

The information in this document is subject to change without notice.
Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.