


100M Unmanaged PoE Switch

S1000-P Series

Overview

BDCOM S1000-P Series is a multi-functional 100M PoE switch introduced by BDCOM. The product is primarily applied in access layer of CCTV and WLAN. S1000 Series includes two models: S1000-4P2F and S1000-8P2F, catering to the needs of different-scale deployments in multiple industries such as finance, education, hospitality, healthcare, transportation, energy and manufacturing, empowering the establishment of simplified and secured network.



CCTV-Mate

Highlights

Switching Features

- Non-blocking switching architecture, and line-speed forwarding of all ports
- Large buffer design, ensures smooth playback of high-definition videos
- Supports IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control
- Multi-functional DIP modes to meet various networking requirements

Practicability

- Plug and play
- LED indicators to show working status

PoE Features

- Compliant with IEEE802.3af/at standards, with a maximum PoE power of 30W per port
- High-power PoE power supply, supporting full load 802.3af on all ports
- Intelligent standard 48V PoE, negotiating power supply based on terminal type
- Supports short-circuit protection and overcurrent protection

Reliability

- Integrated professional lightning protection circuit, with high-level lightning protection
- Built-in high-quality PoE power supply, ensuring safe and stable PoE output
- Compliant with CE and FCC safety standards

Model

S1000-4P2F



- 4-Port 100M PoE+ 2-Port 100M RJ45
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 1 to 4 port extension
 - VLAN – 1 to 4 port isolation
- Dimensions (WxDxH): 200x118x44mm

S1000-8P2F



- 8-Port 100M PoE+ 2-Port 100M RJ45
- Built-in AC power supply
- DIP mode:
 - Default - Standard operating mode
 - CCTV – 1 to 8 port extension
 - VLAN – 1 to 8 port isolation
- Dimensions (WxDxH): 200x118x44mm

Specifications

Item	S1000-4P2F	S1000-8P2F
Switching capacity	1.2Gbps	2Gbps
MAC	1K	2K
Buffer size	448Kb	448Kb
PoE Port	4 100M	8 100M
Uplink RJ45	2 100M	2 100M
Dimensions (mm)	200x118x44	200x118x44
PoE budget	≤60W	≤90W
PoE standard	802.3af/at, maximum output of 30W per port	
Power supply	Built-in AC: 100~240V, 50/60Hz	
Working mode	VLAN mode, Default mode, CCTV mode.	
Environment requirements	Operating temperature/humidity: 0°C-50°C, 10%-90% non-condensing Storage temperature/humidity: -40°C -70°C, 5%-95% non-condensing	
Fan	Fanless	
Lightning protection	6KV	

Ordering Information

S1000-4P2F	4-Port 100M PoE+ 2-Port 100M RJ45 Unmanaged PoE Switch, DIP function, built-in AC220V power supply, PoE budget 60W, desk-top installation
S1000-8P2F	8-Port 100M PoE+ 2-Port 100M RJ45 Unmanaged PoE Switch, DIP function, built-in AC220V power supply, PoE budget 90W, desk-top installation

Copyright © Shanghai BDCOM Communication Technology Co., Ltd. 2023. All Rights Reserved.

This document is BDCOM Public Information. BDCOM reserves the right to alter, update and otherwise change the information contained in the document from time to time.
www.bdc.com.cn

